



PROALL EXT 1002

Ready to Use Exterior Putty Plaster

PRODUCT DESCRIPTION:

It is a water-based, acrylic emulsion-based, ready-to-use exterior putty product used for repair and filling purposes.

FEATURES:

It provides an easy and fast application.

It is suitable for external conditions.

Creates a smooth surface ready for paint.

It penetrates well on the surfaces it is applied to, adheres very well to the surface, is easy to apply,

It is matte.

It is environmentally friendly.

PRODUCT INFORMATION:

Chemical Base Acrylic Based / Water Based

Appearance / Color Liquid / Cream

PERFORMANCE:

(23°C, 50% RH)

Density 1.80 ±0.2 g / cm³

Ph 8 ± 1

Application thickness max.2 mm

These values have been obtained as a result of laboratory tests carried out in our company and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

USAGE AREAS:

Plaster, concrete, etc. outdoors. It is used in the repair of plates and in plastering works before painting.

APPLICATION INSTRUCTIONS:

Surface; It should be cured, dry and firm. It must be cleaned of residues such as oil, grease, dirt, paint, salt vomit that will prevent adhesion.

It is ready to use.

It is first mixed in its own package with the help of a low-speed mixer. It is applied with a spatula or trowel in two layers to obtain a smooth surface. For the second layer application, the first layer must be waited for completely dry.



PROALL EXT 1002

Ready to Use Exterior Putty Plaster

LIMITATIONS:

Please obey to the application instructions to obtain optimum quality. It should not be applied in very high temperature, direct exposure to sunlight, very windy, rainy weather. It should not be applied on surfaces where there is a danger of frost. The application should be done between +5 C and +30 C. It should not be applied at temperatures below 5°C. Until the product cures (28 days), it should be protected from rain, water, frost and adverse external factors.

CONSUMPTION:

0.65 – 1.25 m² area can be putty with 1 kg in one coat.

PACKAGING:

28 kg plastic bucket
5 kg plastic bucket

SHELF LIFE:

It is 1 year from the date of production in its original packaging in dry and non-humid (temperature between +5 C and +25 C) environments. The lid of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.

SECURITY:

Avoid contact with skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, rinse with plenty of water and seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.