



PROŞAP 1009

*Cement Based
Light Screed*

PRODUCT DESCRIPTION:

Cement-based, easy to spread, hyperplasticizer chemical additives and ceramic sphere, perlite, etc. It is a low consumption, light screed that contains light fillings, does not impose a load on the building, has high compressive strength, can self-leveling.

FEATURES:

It is suitable for floors subject to medium and heavy foot traffic.

It spreads on its own and comes to the balance.

It is suitable for 1-10 mm thickness application without shrinkage cracks.

It has high adherence thanks to the special polymer it contains.

It is abrasion resistant.

PRODUCT INFORMATION:

Chemical Base Cement-based

Appearance / Color Powder / gray

USAGE AREAS:

It is used to create a solid and smooth floor against abrasion and dusting on the floors of all buildings exposed to medium and heavy traffic before the topcoat. It is used under PVC, laminate flooring, wood, carpet, ceramic coating, after floor insulation, for smoothing cement-based surfaces.

APPLICATION INSTRUCTIONS

Surface; It should be cured, dry and solid. It must be cleaned of residues such as oil, grease, dirt, paint, salt vomit that will prevent adhesion. The surface must be roughened. Surface cracked and hollow areas PROREPAIR THIN or PROREPAIR; If the application will be made in environments exposed to high sulphate such as sea water and sewage, it should be repaired with PROREPAIR PLUS at least 24 hours beforehand. Places with high absorbency must be primed with PROGEN. In the last stage before the application, there must be a dust-free surface.

If the floor is a water absorbent floor, it should be moistened and applied. The prepared mortar is poured onto the surface starting from a corner and spreads by itself. The thickness of the self-leveling mortar should be adjusted with a steel trowel. To prevent the formation of air bubbles, the surface is smoothed with a spiked roller. 2-5 cm can be applied. If coating will be done on it, it can be done after 24 hours. It is recommended to complete the process within 15-20 minutes. Expired mortar should be disposed of.



PROŞAP 1009

*Cement Based
Light Screed*

LIMITATIONS:

Please obey to the application instructions to obtain optimum quality. The application should be done between +5 C and +30 C. It should not be applied in hot, rainy and windy weather. It should not be applied on surfaces where there is a danger of frost. The product should be protected from rain, water, frost and adverse external factors until it cures (28 days).

CONSUMPTION:

Approx. 8 kg/m² (for 1 cm layer thickness)

PACKAGING:

In 20 kg kraft bags,
(64 pieces per pallet, 1600 kg)

COLOUR:

Grey.

SHELF LIFE:

It is 1 year from the date of production in its original packaging in dry and non-humid (temperature between +5 C and +25 C) environments. The lid of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment.
It should not be left under direct sunlight.

SECURITY:

Since it is cement based, do not breathe the dust, do not contact the skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.