



# PROCONCRETE 1010

*Cement Based  
Decorative Casting Mortar*

## **PRODUCT DESCRIPTION:**

Cement-based, self-leveling, decorative pots, trinkets, sculptures, etc., suitable for use in silicone molds. It is a fast drying casting mortar for products.

## **FEATURES:**

A smooth result is obtained.

Candle holders, candlesticks, flower pots, bowls, vases and many more decorative objects can be made.

It can be painted over after drying.

## **PRODUCT INFORMATION:**

Chemical Base           Cement-Based  
Appearance / Color   Powder / Gray

## **PERFORMANCE:**

(23°C, 50% RH)

Socket start: 5 min

Socket end: 10-15 min

These values have been obtained as a result of laboratory tests carried out in our company and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the environment and the mold volumes will vary, the values may change.

## **USAGE AREAS:**

It is suitable for use for silicone molds.

## **APPLICATION INSTRUCTIONS:**

Clean your casting mold beforehand. The mold must be clean and dry. According to the size of the mold we will pour to make our concrete mortar, 30% of the powder product amount by mass is taken into a container of water. Add PROCONCRETE on it slowly by mixing. It is mixed continuously until it becomes homogeneous and smooth. The prepared concrete mixture is poured into the mold within 3-5 minutes before it hardens. Our concrete will dry after 15-20 minutes, but for best results it is recommended to be removed from the mold the next day. Drying time may vary according to weather conditions and mold. It is recommended to remove the mold after 24 hours.



# **PROCONCRETE**

## **1010**

**Cement Based**  
**Decorative Casting Mortar**

### **LIMITATIONS:**

Please obey to the application instructions to obtain optimum quality. The application should be done between +5 C and +30 C.

### **PACKAGING:**

5 kg plastic bucket  
10 kg plastic bucket

### **COLOUR:**

Grey.

### **SHELF LIFE:**

It is 6 months from the date of production in its original packaging in a humidity-free and dry environment (temperature between +5 C and +25 C). The lid of the containers should be tightly closed when not in use. It should be kept away from moisture.

### **STORAGE CONDITIONS:**

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.

### **SECURITY:**

Since it is cement based, do not breathe the dust, do not contact the skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

*DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.*