



PROWOOD PAINT

526

Wood Look Exterior Paint

PRODUCT DESCRIPTION:

It is a water-based, acrylic emulsion-based, specially developed, flexible and semi-gloss, top coat exterior paint with wood appearance.

FEATURES:

- It has high covering power.
- Its adherence is high.
- It is resistant to rain.
- It is matte.
- Easy to apply.
- It is environmentally friendly.

PRODUCT INFORMATION:

Chemical Base Styrene Acrylic Based / Water Based
Appearance / Color Liquid / Brown&Yellow
Ph 7-10
Density 1.30±0.2g/cm³

PERFORMANCE:

(23°C, 50% RH)

Gloss G2 TS 4318 EN ISO 2813
Grain Size S 1 TS 2620 EN ISO 1524
Water Transfer Rate W2 TS EN 1062-3

These values have been obtained as a result of laboratory tests carried out in our company and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

USAGE AREAS:

It is applied on smooth surfaces on interior and exterior facades. If the application area is rough, PROPLASTER 525 plaster is applied and then applied on it.



PROWOOD PAINT

526

Wood Look Exterior Paint

APPLICATION INSTRUCTIONS:

Surface; It should be cured, dry and solid. It must be cleaned of residues such as oil, grease, dirt, paint, salt vomit that will prevent adhesion. The surface must be rough. If there are significant defects on the application surface, they should be repaired with PROREPAIR THIN at least 24 hours beforehand.

PROPLASTER plaster is applied. When drying occurs after 24 hours, PROTHERM PRIMER is applied.

PROTWOOD PAINT Exterior Paint is diluted with 10-15% water and mixed with the help of a low speed mixer.

Application Equipment:

Hand Mixer
Roll

24 hours before PROTHERM Primer is in the appropriate color (the primer color is important, some parts of the patterned areas will be visible when the application is finished) It is applied as a thick layer on the surface primed with exterior primer. obtained.

LIMITATIONS:

Please obey to the application instructions to obtain optimum quality. The application should be done between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces with frost risk. The product should be protected from rain, water, frost and adverse external factors until it cures (28 days).

CONSUMPTION:

7-9 m²/lt in one coat depending on the absorbency of the surface

PACKAGING:

7.5 lt plastic bucket
15 lt plastic bucket

SHELF LIFE:

It is 1 year from the date of production, in dry and humid environments, out of direct sunlight, in its original package with the lid closed, at +5 ° - 25 °C temperature, 50% relative humidity. When not in use, the lids of the packages should be tightly closed. It should be kept away from moisture. Protect from high heat and frost.



PROWOOD PAINT

526

Wood Look Exterior Paint

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.

SECURITY:

Do not breathe the product, do not contact the skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, rinse with plenty of water and seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.

DEKOSTAR San. ve Tic. Ltd. Şti
Karahıdır Mah. Yolu Üzeri No.:78 Gürsu - BURSA / TÜRKİYE
Tel: (+90) 516 168 61 01 / 850 888 61 00
www.barskimya.com info@barskimya.com