



PROBRICK ADHESIVE

536

Brick Knitting Mortar

GENERAL INFORMATION:

It is a cement-based, polymer-added, water-repellent, thick-textured, factory-mixed masonry mortar that can be applied by hand.

FEATURES

This factory-mixed product is more resistant to water than the mortars prepared by the classical method, thanks to water-repellent additives. At the same time, it provides trouble-free application with its standard high quality at every point.

PRODUCT INFORMATION:

Chemical Base Cement-based

Appearance / Color Powder / Gray

PERFORMANCE:

(23°C, 50% RH)

Maximum Grain size 4 mm

Processing Time 180 min

Compressive Strength 5-6 N/mm²

Temperature resistance after application: (-30°C) – (+80°C)

These values have been obtained as a result of laboratory tests carried out in our company and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

DEKOSTAR San. ve Tic. Ltd. Şti

Karahıdır Mah. Yolu Üzeri No.:78 Gürsu - BURSA / TÜRKİYE

Tel: (+90) 516 168 61 01 / 850 888 61 00

www.barskimya.com info@barskimya.com



PROBRICK ADHESIVE

536

Brick Knitting Mortar

USAGE AREAS:

It can be used in all buildings, interior and exterior.

brick etc. suitable for non-absorbent masonry elements.

APPLICATION INSTRUCTIONS:

Slowly pour 25 kg of PROBRICKADHESIVE onto 6-6.5 liters of water and mix for at least 3-4 minutes in a concrete mixer, electric mixer or continuous mixer until no lumps remain.

Let the mortar rest for 5-10 minutes to mature. It is mixed again before starting the application. Concrete etc. manufacturer's application instructions should be observed.

Prepared mortar is applied to horizontal and/or vertical surfaces with a trowel. With the plastic mallet, the stones are placed in place and smoothness is ensured. The application should be done on the entire surface and the joints should be completely closed.

Application Equipment:

Hand Mixer

Trowel

Knob

LIMITATIONS:

Please obey to the application instructions to obtain optimum quality. The application should be done between +5 C and +30 C. It should not be applied in hot, rainy and windy weather. It should not be applied on surfaces where there is a danger of frost. It should be protected from rain, water, frost and negative external factors for the first 24 hours during and after the application. Application should not be made on surfaces with air outlet without ventilation shaft. The next layer/product application should not be started before the products are completely dry (the duration of which may change under current ambient conditions). No foreign materials or additives should be added to the product during preparation.

DEKOSTAR San. ve Tic. Ltd. Şti

Karahıdır Mah. Yolu Üzeri No.:78 Gürsu - BURSA / TÜRKİYE

Tel: (+90) 516 168 61 01 / 850 888 61 00

www.barskimya.com info@barskimya.com



PROBRICK ADHESIVE

536

Brick Knitting Mortar

CONSUMPTION:

Approx. 17 kg/m² for 10 mm application thickness

Consumption amount, brick used etc. It varies according to the surface areas of the products, their thickness and the way the mortar is applied on them.

PACKAGING:

25 kg kraft bag

SHELF LIFE:

It is 1 year from the date of production in its original packaging in dry and non-humid (temperature between +5 C and +25 C) environments. The lid of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.

SECURITY:

Avoid contact with skin and eyes. Use protective gloves, goggles, mask and clothing. In case of eye contact, seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.

DEKOSTAR San. ve Tic. Ltd. Şti

Karahıdır Mah. Yolu Üzeri No.:78 Gürsu - BURSA / TÜRKİYE

Tel: (+90) 516 168 61 01 / 850 888 61 00

www.barskimya.com info@barskimya.com