



# PRONON MMA 662

Acrylic Based Non-Slip Rough  
Stair & Floor Paint

## **PRODUCT DESCRIPTION:**

It is a Thermoplastic Resin-based paint with high strength, which creates a non-slip rough structure on the floor for pedestrian traffic, thanks to the aggregates in its content.

## **FEATURES:**

is long lasting.

Maximum adherence to the applied surface.

It dries fast.

The floor can be opened to pedestrian and/or vehicle traffic 1-2 hours after the application.

It is not affected by UV rays and other atmospheric conditions.

It is not affected by the impacts and abrasions caused by pedestrian and vehicle traffic.

It is resistant to abrasions caused by stacking machines such as forklifts and pallet trucks. It is not affected by chemicals, exhaust and oil.

It has thermoplastic stretching ability that enables it to work together with the substrate.

## **PRODUCT INFORMATION:**

Chemical Base Thermoplastic Resin Based  
Appearance / Color Liquid / Contact

## **PERFORMANCE:**

(23°C, 50% RH)

Density 1.30 ±0.2 g / cm<sup>3</sup>

Pot Life 15 min.

Commissioning Time 1 h

These values have been obtained as a result of laboratory tests carried out in our company and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

## **USAGE AREAS:**

Asphalt, concrete, helicopter concrete, concrete with surface hardener, mosaic, eposi etc. It can be used easily on surfaces.

Fuel is required, in shopping malls, schools, open and closed car parks of workplaces, residences and shopping malls,

It is used on shipment and parking ramps, factory walkways, forklift roads and acceptance ramps.



# **PRONON MMA**

## **662**

**Acrylic Based Non-Slip Rough  
Stair & Floor Paint**

### **APPLICATION INSTRUCTIONS:**

The surfaces must be clean, smooth, solid, free from all kinds of dust, oil, dirt, rust, mold oil, detergent, etc. The concrete floor should also be free of puddles, moisture and dampness. It should be a dry ground, the concrete surface moisture should be below 4%. It should be prepared by cleaning with suitable mechanical surface preparation techniques such as high pressure water jet, vacuum, roughening, sandblasting.

It is mixed with a low-speed mixer in a clean container free of all kinds of non-adhesive substances or in its own package until a lump-free homogeneous mixture is obtained. It is very important to repair and clean the floor before starting the application. A smooth and solid surface should be obtained before non-slip paint. It is recommended to apply PROMET 521 primer on non-absorbent surfaces. The aggregates in its content may have settled at the bottom of the bucket. The bottom area of the bucket should be mixed thoroughly.

### **Application Equipment:**

Hand Mixer  
Brush & Roller  
Spray Equipment

The aggregates contained in PRONON MMA Floor Anti-Slip Paint are sufficient for anti-slip. It should not be practiced in very cold or very hot weather, under extreme sun, extremely windy weather.

### **LIMITATIONS:**

Please obey to the application instructions to obtain optimum quality. It should not be applied in very high temperature, directly exposed to sunlight, very windy, rainy weather. Application should not be made on surfaces where there is danger of frost at the time of application. The application should be done between +5 C and +30 C. It should not be applied at temperatures below 5°C. It should be protected from rain, water, frost and negative external factors for 24 hours after the application.

### **CONSUMPTION:**

0.300 – 0.500 g/m<sup>2</sup>

### **PACKAGING:**

10 kg tin packaging  
3 kg tin packaging



## **PRONON MMA**

### **662**

**Acrylic Based Non-Slip Rough  
Stair & Floor Paint**

#### **SHELF LIFE:**

It is 1 year from the date of production in its original packaging in dry and non-humid (temperature between +5 °C and +25 °C) environments. The lid of the containers should be tightly closed when not in use. It should be kept away from moisture.

#### **STORAGE CONDITIONS:**

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 °C and +25 °C) environment. It should not be left under direct sunlight.

#### **SECURITY:**

Avoid contact with skin and eyes. Use protective gloves, goggles, mask and clothing. In case of eye contact, seek medical advice immediately. Keep out of reach of children. Avoid skin contact. For detailed information and recommendations, please refer to the Safety Data Sheet.

*DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.*

DEKOSTAR San. ve Tic. Ltd. Şti  
Karahıdır Mah. Yolu Üzeri No.:78 Gürsu - BURSA / TÜRKİYE  
Tel: (+90) 516 168 61 01 / 850 888 61 00  
[www.barskimya.com](http://www.barskimya.com) [info@barskimya.com](mailto:info@barskimya.com)

