



**PROKIM**  
**803**  
**Cream Dye**

**GENERAL INFORMATION:**

Thermoplastic Resin based, solvent based, single component, fast drying, resistant to all weather conditions; It is a new generation strong CREAM PAINT developed for painting red cream, concrete, stone and all mineral-based roofing types.

CREAM PAINT, sun, snow, rain etc. It has maximum resistance against the abrasive effects of weather conditions. It dries quickly thanks to its cellulosic chemical components.

Its application is very simple. It has a waterproof and flexible structure. It fills and closes the fine cracks in the creams. It does not create extra labor costs, anyone can easily apply it.

**FEATURES:**

It is very easy to apply and does not require extra mastery.

Contributes to waterproofing and is waterproof.

It has high covering power.

It is resistant to snow, rain, sun and water.

Quick and easy to apply.

Does not turn yellow or fade over time.

It is resistant to abrasion.

It is not affected by foot traffic.

It can be used on vertical and horizontal surfaces such as walls and ceilings.

It covers the surface perfectly homogeneously.

**PRODUCT INFORMATION:**

Chemical Base thermoplastic acrylate hybrid based / Solvent based

Appearance / Color Liquid / Contact

Density 1.30 ±0.2 g / cm<sup>3</sup>

**PERFORMANCE:**

(23°C, 50% RH)

Density 1.30 ±0.2 g / cm<sup>3</sup>

These values were obtained as a result of laboratory tests carried out in our company at 23°C, 50% relative humidity and are valid for the performance of finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.



**PROKIM**  
**803**  
**Cream Dye**

**USAGE AREAS:**

All cream types with absorbent surface

**APPLICATION INSTRUCTIONS:**

Surface; It should be cured, dry and solid. It must be freed from residues such as oil, grease, dirt, dust that will prevent adhesion.

Before painting, rough floors are filled with our PROREPAIR MMA repair mortar and repaired. Cleanliness on the floor is very important. If there are places with oil residue, they should be cleaned with cellulosic thinner. It should not be applied on wet and damp surfaces.

This situation swells

can cause. In addition, floor paint should not be applied thickly. In case of thick application, the paint can not remove the gas in the air and may form air bubbles.

It is ready to use.

400 rpm until the product has a homogeneous consistency. It should be mixed with a rotary mixer until it becomes homogeneous. PROMET 521 is applied directly as two coats after the primer. Airless spraying system is recommended. It dries in about 1 hour.

**Application Equipment:**

Hand Mixer

Brush Roller

Can Be Applied With Spray Equipment

**LIMITATIONS:**

Please obey to the application instructions to obtain optimum quality. It should not be applied in very high temperature, direct exposure to sunlight, very windy, rainy weather.

Application should not be made on surfaces where there is danger of frost at the time of application. The application should be done between +5 C and +30 C. It should not be applied at temperatures below 5°C. It should be protected from rain, water, frost and negative external factors for 24 hours after the application.

**CONSUMPTION:**

200-300 gr/m<sup>2</sup>



**PROKIM**  
**803**  
**Cream Dye**

**PACKAGING:**

10 kg tin packaging

20 kg tin packaging

**SHELF LIFE:**

It is 1 year from the date of production in its original packaging in dry and non-humid (temperature between +5 C and +25 C) environments. The lid of the containers should be tightly closed when not in use. away from moisture should be kept.

**STORAGE CONDITIONS:**

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.

**SECURITY:**

Avoid contact with skin and eyes. Use protective gloves, goggles, mask and clothing. In case of eye contact, seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

*DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.*