



# *PROMOLD* *805*

*Anti Mold and Moisture Paint*

## **PRODUCT DESCRIPTION:**

It is an acrylic resin-based solvent-based, very strong insulation paint produced by modifying with special chemicals and polymers to eliminate the moisture and mold problems caused by natural conditions on the interior and exterior walls of buildings.

## **FEATURES:**

PROMOLD prevents the formation of mold in its dry film on the surface it is applied.  
It has high covering power.  
Its adherence is high. It is matte.  
Easy to apply

## **PRODUCT INFORMATION:**

Chemical Base Acrylic resin based / Solvent based  
Appearance / Color Liquid / white

## **PERFORMANCE:**

(23°C, 50% RH)

Gloss G3 TS 4318 EN ISO 2813  
Grain Size S1 TS 2620 EN ISO 1524

These values have been obtained as a result of laboratory tests carried out in our company and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

## **USAGE AREAS:**

On interior and exterior walls,  
In basements, garages or cellars  
North facing interior walls  
It is used in areas with a lot of humidity and humidity.  
On all walls with blackening and mold



# *PROMOLD*

## *805*

*Anti Mold and Moisture Paint*

### **APPLICATION INSTRUCTIONS:**

Surface; It should be cured, dry and solid. It must be cleaned of residues such as oil, grease, dirt, paint, salt vomit that will prevent adhesion. Necessary repairs should be made to all cracks, joints, skirts and damaged leaks. Molds formed are mechanically cleaned. After the surface is completely dry, PROMOLD is applied.

It is ready to use and mixed with a low speed mixer.

It is very easy and economical to repair the damages that occur during use. It is applied in two layers. After the first layer, it is waited for 12 hours to dry and then the second layer is applied.

### **LIMITATIONS:**

In order to obtain optimum quality, please obey to the application instructions. Application should not be made in very high temperature, direct exposure to sunlight, very windy, rainy weather. It should not be applied on surfaces where there is a danger of frost. The application should be done between +5 C and +30 C. It should never be applied at temperatures below 5 C. Until the product cures, it should be protected from rain, water, frost and negative external factors.

### **CONSUMPTION:**

200-300 gr/m<sup>2</sup>

### **PACKAGING:**

1 kg tin

3 kg tin

18 kg tin

### **SHELF LIFE:**

It is 1 year from the date of production in its original packaging in dry and non-humid (temperature between +5 C and +25 C) environments. The lid of the containers should be tightly closed when not in use. It should be kept away from moisture.

### **STORAGE CONDITIONS:**

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.



# *PROMOLD* *805*

*Anti Mold and Moisture Paint*

## **SECURITY:**

Avoid contact with skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, rinse with plenty of water and seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

*DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.*

DEKOSTAR San. ve Tic. Ltd. Şti  
Karahıdır Mah. Yolu Üzeri No.:78 Gürsu - BURSA / TÜRKİYE  
Tel: (+90) 516 168 61 01 / 850 888 61 00  
[www.barskimya.com](http://www.barskimya.com) [info@barskimya.com](mailto:info@barskimya.com)