



PROSELF *826*

Spontaneous Spreading Floor Covering

PRODUCT DESCRIPTION:

Two-component, methyl methacrylate (MMA) based, solvent-free, thin structure applied in 3 mm, high performance and strength on the ground, gaps, cracks, etc. The fields itself can be settled and leveled. Used indoors and outdoors, drying approximately 1 hour after application. Self decking

FEATURES:

It is produced in various ground colors.

It is very long lasting.

Maximum adherence to the applied surface.

It is fluid and dries quickly.

The floor can be opened to pedestrian traffic 1 hour after the application.

It is not affected by UV rays and other atmospheric conditions.

It is not affected by the impacts and abrasions caused by pedestrian and vehicle traffic.

It has thermoplastic stretching ability that enables it to work together with the substrate.

PRODUCT INFORMATION:

Chemical Base MMAbased

Appearance A: Powder / B: Liquid

PERFORMANCE:

(23°C, 50% RH)

Compressive Strength 28 days \geq 50-60 N/mm² TS EN 196-1

Flexural Strength 28 days \geq 5-10 N/mm² TS EN 196-1

Adhesion to Concrete \geq 2 N/mm²

Pot Life 15 min.

Opening to Traffic 1 hour

Mixture density 1.8 gr/cm³

These values have been obtained as a result of laboratory experiments and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.



PROSELF *826*

Spontaneous Spreading Floor Covering

USAGE AREAS:

On the floors of all factories and warehouses that need industrial flooring as a seamless and non-porous hygienic floor covering from wall to wall taking the time to renew the coating on the floor, not likely to close the area for fields

Resistant to all kinds of atmospheric, sea conditions, vibrations of the interior and exterior areas of the ship decks.

for a fully durable and optimal pedestrian and working safety coating.

For all areas that want to have chemical flooring in the outside area

Due to the existence of machines that will cause vibration on the ground around, under constant vibration.

for fields

Permanently solve the infiltration of water into the balcony ceiling of the lower floor of balconies and open terraces for

APPLICATION INSTRUCTIONS:

Surface; It must be dry, sound and free of dust. It should be free from residues such as oil, grease, dirt, paint, salt vomit and dust that will prevent adhesion.

Slowly pour component B into component A. Mix with a low-speed electric mixer until the mixture in the cloudy appearance reaches a completely homogeneous appearance. It is poured on the floor and spread with a steel trowel, and immediately after that, a spiked roller is passed over it, helping to expel the air bubbles and leveling the floor.

Application Equipment:

hand mixer

Steel Trowel

Hedgehog Roll

Depending on the temperature of the prepared mortar, maximum 15 minutes. If your application area is small, if you think that one set will be too much, take 50 percent of both components in a different container and mix, you will use half of the product and the other half can stored in their original packages by closing the lids tightly and storing them under suitable conditions. You can use them later. The expired mortar should be disposed of.



PROSELF 826

Spontaneous Spreading Floor Covering

LIMITATIONS:

Please obey to the application instructions to obtain optimum quality. Application +5 C and It should be done between +30 C. It should not be applied in hot, rainy and windy weather. It should not be applied on surfaces where there is a danger of frost. Rain until the product cures,
It should be protected from water, frost and negative external factors.

CONSUMPTION:

Depending on application thickness and floor Approximately 3-5 kg/m²

PACKAGING:

A: 15 kg
B: 5 kg
Total: 20 kg

SHELF LIFE:

It is 1 year from the date of production in its original packaging in dry and non-humid (temperature between +5 C and +25 C) environments. The lid of the containers should be tightly closed when not in use.

It should be kept away from moisture.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.

SECURITY:

Do not breathe the product, use a mask. Avoid contact with skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.