



PROCOURT *835*

Tennis Court & Sports Fields Paint

PRODUCT DESCRIPTION:

It is a water-based resin-based decorative tennis court and sports field paint with high adhesion strength, high UV resistance, non-fading and non-yellowing resistance.

FEATURES:

- It has high covering power.
- It is resistant to rain and water.
- It is applied quickly and easily.
- It has high mechanical strength.
- It does not turn yellow or fade over time.
- It is resistant to abrasion.
- It is not affected by human and vehicle traffic.
- It can be used on vertical and horizontal surfaces.
- It covers the surface perfectly homogeneously.
- It is applied quickly.
- It prevents dusting.
- It looks shiny.

PRODUCT INFORMATION:

Chemical Structure Acrylic Based
Appearance / Color Liquid / Contact
Density $1.30 \pm 0.2 \text{ g / cm}^3$

PERFORMANCE:

(23°C, 50% RH)

Density $1.30 \pm 0.2 \text{ g / cm}^3$

These values have been obtained as a result of laboratory tests carried out in our company and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

USAGE AREAS:

- Tennis Courts
- Sports Fields
- Parking Areas
- School Gardens
- Walking Paths



PROCOURT

835

Tennis Court & Sports Fields Paint

APPLICATION INSTRUCTIONS:

The surface to be applied must first be dry and solid. It should be free of gravel and dust. Broken areas should be fixed. Loose floors should be reinforced beforehand.

It is ready to use.

PROCOURT is ready to use. Before starting the application, the product should be mixed for at least 3-4 minutes with the help of a low-speed mixer until a homogeneous mixture is obtained. It is applied in two coats with a brush, roller or suitable spray equipment. Wait 24 hours between coats.

LIMITATIONS:

Please obey to the application instructions to obtain optimum quality. It should not be applied in very high temperature, direct exposure to sunlight, very windy, rainy weather. It should not be applied on surfaces where there is a danger of frost. The application area should not be exposed to excessive load traffic. The application should be done between +5 C and +30 C. It should not be applied at temperatures below 5°C. Until the product cures (28 days), it should be protected from rain, water, frost and adverse external factors.

CONSUMPTION:

300-500 gr/m²

PACKAGING:

18 kg bucket

SHELF LIFE:

It is 1 year from the date of production in its original packaging in a moisture-free and dry environment. The lid of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.



PROCOURT *835*

Tennis Court & Sports Fields Paint

SECURITY:

Avoid contact with skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, rinse with plenty of water and seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product

DEKOSTAR San. ve Tic. Ltd. Şti
Karahıdır Mah. Yolu Üzeri No.:78 Gürsu - BURSA / TÜRKİYE
Tel: (+90) 516 168 61 01 / 850 888 61 00
www.barskimya.com info@barskimya.com