



PROROAD PAINT

836

Acrylic Based Road Marking Paint

PRODUCT DESCRIPTION:

It is an acrylic-based, one-component, cold application road paint that can be easily used indoors and outdoors.

FEATURES:

It is produced in traffic paint colors in accordance with RAL standards.

It dries very fast. (Average within 1 hour)

It is very resistant to UV rays and other atmospheric conditions.

It is very easy to use.

It is not affected by dirt, dust, exhaust, oil.

It has thermoplastic stretching ability that enables it to work together with the substrate.

Since it is a cold application paint, it may occur during application in hot application paint. there are no hazards.

When it needs to be renewed, the old paint does not need to be removed from the surface.

PRODUCT INFORMATION:

Chemical Base Acrylic

Appearance / Color Liquid / Contact.

PERFORMANCE:

(23°C, 50% RH)

Density 1.50±0.2 kg/lit

These values have been obtained as a result of laboratory tests carried out in our company and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

USAGE AREAS:

Asphalt, concrete, surface hardener, mosaic, etc. It can be used easily on surfaces. It is also very ideal for painting paving curbstones.

Line, arrow, pedestrian crossing, letter and number applications can be done easily.

Mainly used areas:

All kinds of military fields,

Airports, ports, shipyards,

All kinds of industrial areas, workshops and warehouses,

Inner and outer city roads, bridges, viaducts, pedestrian roads, landscaping, parking lots,

Health facilities, hospitals, shopping malls, business centers, hotels, resorts,

DEKOSTAR San. ve Tic. Ltd. Şti
Karahıdır Mah. Yolu Üzeri No.:78 Gürsu - BURSA / TÜRKİYE
Tel: (+90) 516 168 61 01 / 850 888 61 00
www.barskimya.com info@barskimya.com



PROROAD PAINT

836

Acrylic Based Road Marking Paint

APPLICATION INSTRUCTIONS:

Before applying PROROAD PAINT, it should be ensured that the surface to be applied is dry, dust-free, free from oil and other dirt. The surface temperature of the road must be above 5 °C. It is recommended to clean the existing paint on the road. However, if the old paint on the surface cannot be easily cleaned, it can be applied on it.

Application Equipment:

Hand Mixer
Spray Equipment

It is recommended to be applied by spraying on the road surface with automatic application equipment and pouring glass beads on it. If necessary, it can also be applied with a brush or roller. Since the product is in application viscosity, there is no need for thinning.

LIMITATIONS:

Please obey to the application instructions to obtain optimum quality. The application should be done between +5 C and +30 C. It should not be applied in hot, rainy and windy weather. It should not be applied on surfaces where there is a danger of frost. The product should be protected from rain, water, frost and adverse external factors until it cures (28 days). Before applying, ask for technical support for ground conditions.

CONSUMPTION:

200-300 gr/m² for 100 micron thickness

PACKAGING:

20 kg tin packaging

SHELF LIFE:

It is 1 year from the date of production in its original packaging in dry and non-humid (temperature between +10 C and +25 C) environments. The lid of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +10 C and +25 C) environment. It should not be left under direct sunlight.



PROROAD PAINT

836

Acrylic Based Road Marking Paint

SECURITY:

Do not breathe the product, use a mask. Avoid contact with skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product

DEKOSTAR San. ve Tic. Ltd. Şti
Karahıdır Mah. Yolu Üzeri No.:78 Gürsu - BURSA / TÜRKİYE
Tel: (+90) 516 168 61 01 / 850 888 61 00
www.barskimya.com info@barskimya.com