



# *PROAC FILLING*

## *838*

*Acrylic Based Filling and Repair Paste*

### **PRODUCT DESCRIPTION:**

It is a water-based, acrylic emulsion-based, ready-to-use, sealed interior and exterior wall putty product used for repair and filling purposes.

### **FEATURES:**

It provides an easy and fast application.

It is suitable for external conditions.

Creates a smooth surface ready for paint.

It penetrates well on the surfaces it is applied to, adheres very well to the surface, is easy to apply,

It is matte.

It is environmentally friendly.

### **PRODUCT INFORMATION:**

Chemical Base Acrylic Based / Water Based

Appearance / Color Liquid / Cream

### **PERFORMANCE:**

(23°C, 50% RH)

Density 1.80 ±0.2 g / cm<sup>3</sup>

Ph 8 ± 1

Application thickness max.2 mm

These values have been obtained as a result of laboratory tests carried out in our company and are valid for the performance of the finished applications at the end of the full drying period.

Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

### **USAGE AREAS:**

In dilatation and expansion joints,

At the bottom of the chimney strainer edges,

In joints and joints, Eternit, aluminum, glass, plastic joinery and edges,

In the joints of coatings such as stone, ceramic, marble, etc., in skirting boards,

Filling or repairing cracks or holes,

It is used in additional joints of prefabricated gutters and facades.



# *PROAC FILLING*

## *838*

*Acrylic Based Filling and Repair Paste*

### **APPLICATION INSTRUCTIONS:**

Surface; It should be cured, dry and sound. It must be cleaned of residues such as oil, grease, dirt, paint, salt vomit that will prevent adhesion.

It is ready to use.

After opening the package, it is mixed for 2 minutes until a homogeneous consistency is obtained. If a dilatation or expansion joint is being made, it is recommended to put a PE filler wick on the joint beforehand and apply it on it. It is recommended to use with joint mesh in chamfer detail applications. The ready-to-use PROAC FILLER is filled onto the existing prepared surface with the help of a spatula or a mouth-filling sealant pump. After filling, the surface is smoothed with a wet sponge. PROAC FILLER should not be applied more than 5mm in one go.

### **LIMITATIONS:**

Please obey to the application instructions to obtain optimum quality. It should not be applied in very high temperature, direct exposure to sunlight, very windy, rainy weather. It should not be applied on surfaces where there is a danger of frost. The application should be done between +5 C and +30 C. It should not be applied at temperatures below 5°C. Until the product cures (28 days), it should be protected from rain, water, frost and adverse external factors.

### **CONSUMPTION:**

0.65 – 1.25 m<sup>2</sup> area can be putty with 1 kg in one coat.

### **PACKAGING:**

1 kg plastic bucket  
5 kg plastic bucket  
10 kg plastic bucket

### **SHELF LIFE:**

It is 1 year from the date of production in its original packaging in dry and non-humid (temperature between +5 C and +25 C) environments. The lid of the containers should be tightly closed when not in use. It should be kept away from moisture.

### **STORAGE CONDITIONS:**

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.



# *PROAC FILLING*

## *838*

*Acrylic Based Filling and Repair Paste*

### **SECURITY:**

Avoid contact with skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, rinse with plenty of water and seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

*DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product*

DEKOSTAR San. ve Tic. Ltd. Şti  
Karahıdır Mah. Yolu Üzeri No.:78 Gürsu - BURSA / TÜRKİYE  
Tel: (+90) 516 168 61 01 / 850 888 61 00  
[www.barskimya.com](http://www.barskimya.com) [info@barskimya.com](mailto:info@barskimya.com)