



PROGEN PR 860

General Primer for Cementitious Products

PRODUCT DESCRIPTION:

PROGEN PR is a water-based acrylic emulsion-based mortar binder product used on concrete, screed and cement-based surfaces.

FEATURES:

It creates a strong bond between old concrete and screed.
It is waterproof.
It is resistant to frost.
It is suitable for indoor and outdoor use.

PRODUCT INFORMATION:

Chemical Base Acrylic based / Water based
Appearance / Color Liquid / White
Dry Film Color Transparent

PERFORMANCE:

(23°C, 50% RH)

Ph 7-10

Density 1.0 ±0.2 g / cm³

These values have been obtained as a result of laboratory tests carried out in our company and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

USAGE AREAS:

Indoors and outdoors
Before screed
It is used before the use of repair mortar.

APPLICATION INSTRUCTIONS:

PROGEN PR is ready to use. It can be applied by direct application or spraying without adding any additives.

Application Equipment:

Roller Brush
Spray Equipment

PROGEN PR should be shaken before use. The product should be applied homogeneously on the floor with a roller, brush or spray equipment. Pond should not be caused.

DEKOSTAR San. ve Tic. Ltd. Şti
Karahıdır Mah. Yolu Üzeri No.:78 Gürsu - BURSA / TÜRKİYE
Tel: (+90) 516 168 61 01 / 850 888 61 00
www.barskimya.com info@barskimya.com



PROGEN PR 860

General Primer for Cementitious Products

No contribution should be made. A single layer application is made. It can be applied to absorbent surfaces in two coats. The second coat should be applied after 24 hours.

LIMITATIONS:

Please obey to the application instructions to obtain optimum quality. The application should be done between +5 C and +30 C. It should not be applied in hot, rainy and windy weather. It should not be applied on surfaces where there is a danger of frost. The product should be protected from rain, water, frost and adverse external factors until it cures (28 days).

CONSUMPTION:

150-250 g/m² depending on the absorbency of the surface

PACKAGING:

5 kg bag drum
30 kg bag drum.

SHELF LIFE:

It is 1 year from the date of production in its original packaging in dry and non-humid (temperature between +5 C and +25 C) environments. The lid of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment.
It should not be left under direct sunlight.

SECURITY:

Avoid contact with skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, rinse with plenty of water and seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product