



PROCONTACT
PR 865
Gross Concrete Primer

PRODUCT DESCRIPTION:

It is a water-based, acrylic emulsion-based, exposed concrete surface primer containing special aggregates with high scratch resistance.

FEATURES:

It increases the adhesion strength and surface adherence by creating a rough surface for plasterboard bonding on smooth exposed concrete floors.

It is ready to use.

It is environmentally friendly.

PRODUCT INFORMATION:

Chemical Base Acrylic BASED / Water BASED

Aggregate Structure Basalt

Appearance / Color Liquid / Yellow

PERFORMANCE:

(23°C, 50% RH)

Ph 7-10

Density 1.40 ±0.2 g / cm³

Grain Size S4 TS 2620 EN ISO 1524

These values have been obtained as a result of laboratory tests carried out in our company and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

USAGE AREAS:

It is used on exposed concrete surfaces used in areas such as walls, columns, ceilings.

APPLICATION INSTRUCTIONS:

Surface; It should be cured, dry and solid. It must be cleaned of residues such as oil, grease, dirt, paint, salt vomit that will prevent adhesion.

Ready to use.



PROCONTACT

PR 865

Gross Concrete Primer

Application Equipment:

Hand Mixer
Brush
Roll

The product is ready to use, 15 kg of PROCONTACT PR is mixed with a low-speed mixer and applied with a brush or roller. It is recommended to mix with a low speed mixer less than 500 Rpm. Due to the aggregate content, the material in the container should be mixed at intervals during the application. It should not be applied on before it dries. The temperature of the application surface should be between 5°C-30°C and the surface should not receive precipitation. After drying, application should be started after at least 24 hours.

LIMITATIONS:

Please obey to the application instructions to obtain optimum quality. The application should be done between +5 C and +30 C. It should not be applied in hot, rainy and windy weather. It should not be applied on surfaces where there is a danger of frost. Until the product cures (28 days), it should be protected from rain, water, frost and adverse external factors.

CONSUMPTION:

It depends on the absorbency of the surface.

PACKAGING:

15 kg plastic bucket

SHELF LIFE:

It is 1 year from the date of production, in its original packaging with the lid closed, at +5 ° 30°C, 50% relative humidity in dry and damp (temperature between +5 °C and +25 °C) environments out of direct sunlight. When not in use, the lids of the packages should be tightly closed. It should be kept away from moisture. Protect from high heat and frost.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.



PROCONTACT
PR 865
Gross Concrete Primer

SECURITY:

Do not inhale, avoid contact with skin and eyes. Use protective gloves, goggles, mask and clothing. In case of eye contact, rinse with plenty of water and seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product

DEKOSTAR San. ve Tic. Ltd. Şti
Karahıdır Mah. Yolu Üzeri No.:78 Gürsu - BURSA / TÜRKİYE
Tel: (+90) 516 168 61 01 / 850 888 61 00
www.barskimya.com info@barskimya.com