



PROKAP 880

Peelable Surface Protective Coating

PRODUCT DESCRIPTION:

It is a water-based peelable (liquid stretch) protective coating that provides 100% protection against external threats and has the ability to clean the surface on which it is removed.

FEATURES:

- Single component.
- It is based on riding.
- It is easy to use.
- Ready to use.
- Its adherence is high.
- Minimizes repair and repair costs.

PRODUCT INFORMATION:

Chemical Base Water based
Appearance Liquid

PERFORMANCE:

(23°C, 50% RH)

Drying time 30min-120 min

These values have been obtained as a result of laboratory tests carried out in our company and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

USAGE AREAS:

Non-absorbent surfaces such as glass, aluminum and PVC joinery, steel, granite, ceramic, furniture, white goods, parquet.

APPLICATION INSTRUCTIONS:

It is ready to use.

It is applied to the surface with a standard paint roller or a thin brush. Make sure that the wet film thickness is at least 200 microns. If protection is required for heavy conditions, 45 minutes. then apply one more coat. It can also be applied using an airless gun. While applying, ensure homogeneity on the surface by throwing one hand horizontally and then one vertically. Wait for it to dry on the surface.

After drying, it is removed from the corner and peeled off.



PROKAP 880

Peelable Surface Protective Coating

LIMITATIONS:

In order to obtain optimum quality, please obey to the application instructions. The application should be done between +5 C and +30 C. It should not be applied in hot, rainy and windy weather. It should not be applied on surfaces where there is a danger of frost. Until the product cures, it should be protected from rain, water, frost and negative external factors.

CONSUMPTION:

150-250 gr / m² for 200 micron thickness

PACKAGING:

5 kg plastic bucket
15 kg plastic bucket

SHELF LIFE:

It is 1 year from the date of production, in dry and humid environments, out of direct sunlight, in its original package with the lid closed, at +5 ° - 25 °C temperature, 50% relative humidity. When not in use, the lids of the packages should be tightly closed. It should be kept away from moisture. Protect from high heat and frost.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.

SECURITY:

Do not breathe the product, use a mask. Avoid contact with skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product