



PROTEC
885
Composite Floor Polish

PRODUCT DESCRIPTION:

Resin-based, solvent-based, low-viscosity, mineral-based, new generation floor polish that can penetrate deep into the pores on the surface and gives anti-dusting shine.

FEATURES:

- Single component.
- It is based on riding.
- It is easy to use.
- Ready to use.
- Its adherence is high.
- It can be deleted. It does not hold dirt.
- Creates glossy film.
- It dries fast.

PRODUCT INFORMATION:

Chemical Base Resin based / Solvent Based
Appearance / Color Liquid / Close To Transparent.

USAGE AREAS:

It is applied after cement based floor coverings.
On cement coated floors in commercial and private residences
On the floors of factories, warehouses, parks, parking lots, car repair shops, train stations and logistics centers in open and closed areas
On the floors of show halls, restaurants, event and convention centers or museums

APPLICATION INSTRUCTIONS:

Surface; It should be cured and strong, loose surfaces, mortar, concrete pieces, etc. are cleaned and the surface is strengthened. It must be cleaned of residues such as oil, grease, dirt, paint, salt vomit that will prevent adhesion.

Ready to use .

Application Equipment:

- Hand Mixer
- Roll



PROTEC
885
Composite Floor Polish

PROTEC is ready to use. The product is stirred at 400-600 rpm with the help of a medium speed mixer. It is mixed rapidly until a homogeneous mixture is obtained. It is applied with a roller. Thin 2 coats are recommended. The first floor strengthens the floor by filling the pores. The second coat increases scratch and abrasion resistance. It creates a homogeneous, shiny surface on the floor.

LIMITATIONS:

In order to obtain optimum quality, please obey to the application instructions. The application should be done between +5 C and +30 C. It should not be applied in hot, rainy and windy weather. It should not be applied on surfaces where there is a danger of frost. The product should be protected from rain, water, frost and adverse external factors until it cures (28 days).

CONSUMPTION:

Two coats of 100gr/m²

PACKAGING:

5 kg tin packaging

15 kg tin packaging

SHELF LIFE:

It is 1 year from the date of production, in dry and humid environments, out of direct sunlight, in its original package with the lid closed, at +5 ° - 25 °C temperature, 50% relative humidity. When not in use, the lids of the packages should be tightly closed. It should be kept away from moisture. Protect from high heat and frost.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.



PROTEC
885
Composite Floor Polish

SECURITY:

Do not breathe, use mask. Avoid contact with skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product

DEKOSTAR San. ve Tic. Ltd. Şti
Karahıdır Mah. Yolu Üzeri No.:78 Gürsu - BURSA / TÜRKİYE
Tel: (+90) 516 168 61 01 / 850 888 61 00
www.barskimya.com info@barskimya.com