



PROCLEAN 888

*Joint and Cement Residue
Cleaning Chemical*

PRODUCT DESCRIPTION:

Ceramic, marble etc. It is an acid-containing liquid cleaning material used for removing stains and cement residues formed in the joints of coating materials and joint fillers.

FEATURES:

Single component.

It is easy to use.

Ready to use.

It is also effective on natural dirt.

Thanks to its natural content, it does not corrode the grouting surface.

It is suitable for indoor and outdoor use on horizontal and vertical surfaces.

PRODUCT INFORMATION:

Chemical Base

Acidic

Appearance / Color

Liquid / Close To Transparent.

PERFORMANCE:

(23°C, 50% RH)

pH value: 1-2

These values have been obtained as a result of laboratory experiments and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

USAGE AREAS:

It is used on ceramics and joint fillings.

Not suitable for use on marble, granite and natural stone.

APPLICATION INSTRUCTIONS:

The surface must be dry.

Ready to use .

PROCLEAN is sprayed liberally on the heavily soiled surface. It is expected to swell. After 3-5 minutes, it is wiped off with a sponge. The last remaining dirty places should be cleaned by gently rubbing. Finally, the entire area is washed with water and left to dry.



PROCLEAN 888

**Joint and Cement Residue
Cleaning Chemical**

LIMITATIONS:

For use in coating materials it is recommended to test on a small area. In order to obtain optimum quality, please obey to the application instructions. The application should be done between +5 C and +30 C.

CONSUMPTION:

It depends on the dirty surface area and the amount of dirt.

PACKAGING:

500 g spray bottle

5 kg plastic drum

SHELF LIFE:

It is 1 year from the date of production, in dry and humid environments, out of direct sunlight, in its original package with the lid closed, at +5 ° - 25 °C temperature, 50% relative humidity. When not in use, the lids of the packages should be tightly closed. It should be kept away from moisture. Protect from high heat and frost.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.

SECURITY:

Do not breathe, use mask. Avoid contact with skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. It should not come into contact with reactive metals, bleach (bleach), ammonia and bases. Avoid contact with metal surface. The environment should be ventilated during the application. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.