



***PROTHERM
PRIMER 980***
Interior and Exterior Paint Primer

PRODUCT DESCRIPTION:

It is a water-based, acrylic emulsion-based interior and exterior paint primer.

FEATURES:

- It is used as a first coat primer on plaster and concrete-like surfaces.
- It reduces the consumption of topcoat paints.
- It prepares a healthy ground.
- Its adherence is high.
- It can be used easily on old painted exterior surfaces.
- Easy to apply.
- It is environmentally friendly.

PRODUCT INFORMATION:

Chemical Base Styrene Acrylic based / Water based
Appearance / Color Liquid / White
Ph 7-10
Density 1.30±0.2g/cm³

PERFORMANCE:

(23°C, 50% RH)
Gloss G3 TS 4318 EN ISO 2813
Grain Size S1 TS 2620 EN ISO 1524

These values have been obtained as a result of laboratory experiments carried out in our company and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

USAGE AREAS:

On exteriors; It is used before painting on concrete, brick, cement-based plaster, gas concrete etc. surfaces.



***PROTHERM
PRIMER 980***
Interior and Exterior Paint Primer

APPLICATION INSTRUCTIONS:

Surface; It should be cured, dry and solid. It must be cleaned of residues such as oil, grease, dirt, paint, salt vomit that will prevent adhesion. The surface must be rough. If there are significant defects on the application surface, they should be repaired with PROREPAIR THIN or PROREPAIR, PROREPAIR PLUS at least 24 hours in advance. PROTHERM PRIMER Exterior primer is ready to use. If desired, 10% water can be added and mixed with a low-speed mixer.

Application Equipment:

Hand Mixer
Roll

The prepared mixture is applied with a clean roller on the surface preparation area.

LIMITATIONS:

Please obey to the application instructions to obtain optimum quality. The application should be done between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces with frost risk. The product should be protected from rain, water, frost and adverse external factors until it cures (28 days).

CONSUMPTION:

10-12 m²/lt in one coat, depending on the absorbency of the surface

PACKAGING:

15 lt plastic bucket

SHELF LIFE:

It is 1 year from the date of production in a dry and moisture-free environment, out of direct sunlight, in its original package with the lid closed, at +5 ° - 25 °C temperature, 50% relative humidity. When not in use, the lids of the packages should be tightly closed. It should be kept away from moisture. Protect from high heat and frost.



***PROTHERM
PRIMER 980***
Interior and Exterior Paint Primer

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.

SECURITY:

Do not inhale, avoid contact with skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, rinse with plenty of water and seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.