



PROFACADE

981

**Thermal Insulation
Coating Primer**

PRODUCT DESCRIPTION:

It is an acrylic copolymer emulsion based primer developed for pre-coating in white color heat insulation systems with high adherence strength.

FEATURES:

PROKREPI facilitates patterning during coating application.
It prevents the dirt and stains on the surface from getting on the PROKREPI Coating.
It has high closing power. It hardens the application surface.
It reduces the water absorbency of the surface. It makes the surface homogeneous for coating.
Matte white color

USAGE AREAS:

It is used before coating applications on thermal insulation systems and on previously painted or unpainted exterior and interior surfaces.

APPLICATION INSTRUCTIONS:

The surfaces on which the Coating Primer will be applied must be free of all kinds of pollution and dry. The primer is applied directly with either a brush, roller or spray application. Mix before application. During the application, make sure that the surface and air temperature is between +5°C and +30°C. Do not apply on very hot surfaces exposed to rain or direct sun. We recommend that you do it 1 day before the coating application and as a single layer. The primer is produced in white color. If the color tone is desired, you can use the coloring tubes to ensure that it is suitable for the coating color to be applied on, and you can add 5% colorant to the primer at most.

Application Equipment:

Roller, brush, spray

LIMITATIONS:

Initial Dry at 20°C and HR: 65%: 1 hour; Final Drying: 24 hours, Coating is applied after 12 hours.

CONSUMPTION:

Coating Primer 200-300 gr/m² in one coat. It should be taken into account that the consumption amounts specified may differ depending on the surface and application conditions.



PROFACADE 981

Thermal Insulation
Coating Primer

PACKAGING:

15 kg plastic bucket

SHELF LIFE:

It can be stored for 1 year in its unopened package, in a cool place, protected from direct sunlight and frost.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.

SECURITY:

Do not breathe the product, do not contact the skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, rinse with plenty of water and seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.