



PROCOLOR
995
Ceiling & Wall Paint

PRODUCT DESCRIPTION:

It is a water-based, acrylic emulsion-based, silicone-reinforced top coat ceiling and wall paint.

FEATURES:

It has high covering power.

Its adherence is high.

Easy to apply.

It is environmentally friendly.

PRODUCT INFORMATION:

Chemical Base Styrene Acrylic based / Water based

Appearance / Color Liquid / Desired

Ph 7-10

PERFORMANCE:

Gloss G3 TS 4318 EN ISO 2813

Grain Size S 1 TS 2620 EN ISO 1524

Water Vapor Transfer V 1 TS EN ISO 7783-2

Water Transfer Rate W2 TS EN 1062-3

Dry Film Thickness E 3 TS EN 1062-1

Density 1.30±0.2g/cm³



PROCOLOR
995
Ceiling & Wall Paint

These values have been obtained as a result of laboratory experiments and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

USAGE AREAS:

It is used on cement-based plaster, concrete etc. surfaces primed on all interior facades.

APPLICATION INSTRUCTIONS:

Surface; It should be cured, dry and solid. It must be cleaned of residues such as oil, grease, dirt, paint, salt vomit that will prevent adhesion. The surface must be primed. If there are significant defects on the application surface, apply the appropriate repair material at least 24 hours in advance.

Must be repaired.

PROCOLOR INTERIOR Wall Paint can be thinned with a maximum of 10% water and mixed with a low speed mixer before application.

Application Equipment:

Hand mixer

Roll

Two coats are applied to the primed surface 24 hours before.

LIMITATIONS:

Please obey to the application instructions to obtain optimum quality. The application should be done between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces with frost risk. Until the product cures, it should be protected from rain, water, frost and negative external factors.



PROCOLOR

995

Ceiling & Wall Paint

CONSUMPTION:

7-9 m² in one coat, depending on the absorpency of the surface / lt

PACKAGING:

15 lt plastic bucket

SHELF LIFE:

It is 1 year from the date of production, in dry and humid environments, out of direct sunlight, in its original package with the lid closed, at +5 °-25 °C temperature, 50% relative humidity.

When not in use, the lids of the packages should be tightly closed. It should be kept away from moisture. Protect from high heat and frost.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.

SECURITY:

Do not breathe the product, do not contact the skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, rinse with plenty of water and seek medical advice immediately.

Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.