



PROLASTIC TURBO 245

**Fast Drying at Low Temperatures
Applicable fully elastic Water Insulation
Product**

GENERAL INFORMATION:

It is a two-component, cement-based, fast-drying, gray colored waterproofing mortar that can be applied in winter, containing polymer emulsion and special chemicals.

FEATURES:

- It has high elasticity.
- Crack bridging feature is at the highest level.
- Its adherence is strong.
- It dries quickly, reducing the working time between coats.
- Can be applied to slightly damp surfaces
- Can be applied at low temperatures
- It adheres perfectly to mineral-based surfaces.

PRODUCT INFORMATION:

- Powder Component:
 - Chemical Base Cement-based
 - Appearance / Color Powder / Gray
- Liquid Component:
 - Chemical Base Acrylic based / Water based
 - Appearance / Color Liquid / White
 - Dry Film Color Transparent
 - Ph 5-7

PERFORMANCE:

(23°C, 50% RH)

Dry Bulk Density (powder component) 1650 ± 200 kg/m³ TS EN 1015-10

Density (liquid component) 0.98-1.1 gr/cm³

Crack bridging ≥ 1 mm TS EN 1062-7 (+23 °C)

Capillary water absorption <0.1 kg/m².h0.5 TS EN 1062-3

Adhesion to Concrete ≥ 0.5 MPa TS EN 1542

These values have been obtained as a result of laboratory experiments and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.



PROLASTIC TURBO 245

**Fast Drying at Low Temperatures
Applicable fully elastic Water Insulation
Product**

USAGE AREAS:

On mineral surfaces such as concrete, plaster, screed as a surface
On balconies and terraces, under tiles in wet areas such as bathrooms, toilets and kitchens.
In water tanks
On horizontal and vertical surfaces
It is used in waterproofing of structures above ground in waterproofing from the positive side.
It should not be applied in areas where water is observed from the negative side.

APPLICATION INSTRUCTIONS:

Surface; It should be cured and has to be clean (no cracks). It must be cleaned of residues such as oil, grease, dirt, paint, salt vomit that will prevent adhesion. PROREPAIR THIN or PROREPAIR if the surface is defective; If the application will be made in environments exposed to high sulphate such as sea water and sewage, it should be repaired with PROREPAIR PLUS at least 24 hours in advance. If the area to be applied is on a horizontal floor, it is recommended to apply screed with PROLEVEL beforehand in order to make the surface smooth. Newly plastered areas should be allowed to cure for at least 7 days before application.
It is ready to use.

Application Equipment:

Hand Mixer
Brush
Airless Spray

After making sure that the surface to be applied is dry, the corner joints should be curved with PROBAND. PROBITUM PR Bitumen Primer is applied as a single layer. First of all, it should be applied with a thin brush to the areas where the curving tape is taken. PROBITUM 1K is cold applied. After mixing, it is applied with a bitumen brush, trowel or airless spray. After complete drying, the second coat can be applied. On surfaces exposed to temporary and permanent water pressure, alkali resistant PROTEX glass fiber mesh application should be applied to the entire surface between the first and second coats. Foundation excavation should not be closed until complete drying. Filling should be done after the coating is protected with appropriate thermal insulation and drainage boards. The total application thickness should be determined according to the application area and the water pressure to which the insulation layer will be exposed. Expired mortar should be disposed of.



PROLASTIC TURBO 245

**Fast Drying at Low Temperatures
Applicable fully elastic Water Insulation
Product**

LIMITATIONS:

Please obey to the application instructions to obtain optimum quality. The application should be done between +5 C and +30 C. It should not be applied in hot, rainy and windy weather. It should not be applied on surfaces where there is a danger of frost. It should be protected from rain, water, frost and negative external factors during the application and for the first 24 hours after the application.

CONSUMPTION:

Approximately 1.5-kg / m² for each coat minimum

PACKAGING:

20 KG Plastic Bucket

SHELF LIFE:

It is 1 year from the date of production in its original packaging in dry and non-humid (temperature between +5 C and +25 C) environments. The cover top of the containers should be tightly closed when not in use. Should be kept away from moisture.

STORAGE CONDITIONS:

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.

SECURITY:

Since it is cement based, do not breathe the dust, use a mask. Avoid contact with skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, rinse with plenty of water and seek medical advice immediately. Keep out of reach of children.

In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product.